

bath filler - **Acura Thermostatic TMV3 Bath Filler**

Introduction

Simple to operate and reliable time after time, the acura thermostatic bath filler has been designed to make a statement as well as provide ease of use regardless of the users dexterity. With TMV3 approval Inta's acura thermostatic bath filler is suitable for hospitals, healthcare, nursing homes, sheltered accommodation, hotels and schools whilst meeting the requirements of the building requirements part G section 3 the subtleties of the modern inclusive design mean the bath filler is also the perfect choice for the domestic home.

acura range
with
TMV3 approved
anti scald technology

- Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems
- Thermal cartridge technology
- Fail safe on hot and cold supplies
- Lever handles
- Operating pressure range of 0.2 to 5 bar
- Wall or deck mounted versions available
- WRAS* and TMV3 approved
- Complies with Building Regulations Part G
- Range of showers and basin mixer taps to match



Description	Code
acura thermostatic bath filler (wall mounted)*	AC50010CP
acura thermostatic bath filler with deck mounting legs	AC50020CP



*WRAS approval applicable to AC50010CP only

bath filler - **Acura Thermostatic TMV3 Bath Filler**

Features

■ Technical Specification

Max Inlet Pressure static	5 Bar
Min Inlet Pressure dynamic	0.2 Bar
Max Inlet Temperature	85°C
Factory Pre-set Temperature	41°C
Inlet Connections	G 3/4" F BSP (valve body)
Min Temperature to achieve hot or cold failsafe	15°C
System Installation	Unvented, Pressurised, Gravity and Combination Boilers

