

shower valves - **Vue Safe Touch Thermostatic Bar Shower**

Introduction

Introducing the Vue, the first TMV2 approved valve with a cool body. The Vue brings extra safety and comfort to every bath and shower room

safe touch body
with **total control**



- Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems
- Thermal cartridge technology
- Temperature stability of $\pm 2^{\circ}\text{C}$
- Fail safe protection on both the hot and cold supplies
- Operating pressure range of 0.2 to 5 bar
- Safe touch body

Product Range

Description	Code
Vue safe touch thermostatic bar shower with flexible slide rail kit	VU10014CP
Vue safe touch thermostatic bar shower	VU10010CP
Flexible slide rail kit	31665CPA

vue safe touch thermostatic
bar shower with flexible slide rail kit
VU10014CP



shower valves - **Vue Safe Touch Thermostatic Bar Shower**

Features

▀ Technical Specification

Max Inlet Pressure (static)	5 Bar
Min Inlet Pressure (dynamic)	0.2 Bar
Max Inlet Temperature	85°C
Factory Pre-set Temperature	38°C with max temp stop
Inlet Connections	G 3/4" F BSP (valve body)
Outlet Connections	G 1/2" F BSP
Min Temperature differential to achieve hot or cold failsafe	15°C

System Installation: Unvented, Pressurised, Gravity and Combination Boilers

