

shower valves - **Infiniti Thermostatic Bar Shower**

Introduction

Making a bold statement in a bathroom or shower room will never be a problem with the striking looks of the infiniti range from inta. The sleek lines and flawless finish, coupled with TMV2 approved thermostatic protection means that comfort, safety and style go hand in hand.

total control



- Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems
- Thermal cartridge technology
- Temperature stability of $\pm 2^{\circ}\text{C}$
- Fail safe protection on both the hot and cold supplies
- Operating pressure range of 0.4 to 5 bar
- WRAS and TMV2 approved

Product Range

Description	Code
Infiniti thermostatic bar shower with fixed riser overhead soaker and sliding handset	10070CP

infiniti thermostatic bar shower
with fixed riser, overhead soaker
and sliding handset
10070CP



shower valves - **Infiniti Thermostatic Bar Shower**

Features

Technical Specification

Max Inlet Pressure (static)	5 Bar
Min Inlet Pressure (dynamic)	0.4 Bar
Max Inlet Temperature	85°C
Factory Pre-set Temperature	38°C with max temp stop
Inlet Connections	G 3/4" F BSP (valve body)
Outlet Connections	G 1/2" F BSP
Min Temperature differential to achieve hot or cold failsafe	15°C

System Installation: Unvented, Pressurised, Gravity and Combination Boilers

