

Intafil Combi Sealed System Kit

The all-in-one solution that combines multiple essential components into a single, compact and time-saving assembly. Intafil combi allows you to fill a central heating system and drain the expansion vessel in one easy-to-fit monoblock.



- Supplied with a BS EN ISO 228 G3/4" swivel connection for the expansion vessel
- G1/2" connection for optional safety relief valve
- Provides flexibility for system configuration
- Rotatable drain-off valve enables simple, quick, clean servicing or replacement of the expansion vessel
- BSEN 1252-2 22mm Direct circuit connection removes the need for additional, time-consuming and costly pipework connections
- Anti-tamper isolation valve enhances system safety and compliance while preventing unauthorised adjustment
- G24 WRAS approved filling loop and pressure gauge
- Easy system fill, comply and system pressure monitoring
- Suitable for use with up to 50% glycol solution
- Max static pressure of 16 bar
- Max temperature of 85°C



WARNING! – The installer should be aware that a safety relief valve is installed in the circuit and if in doubt one should be fitted to the Intafil combi.

Code	Description
KTSSK34	3/4" Intafil Combi with Filling Loop & Wall Bracket
KTSSK34NB	3/4" Intafil Combi with Filling Loop
KTSSK34SRV	3/4" Intafil Combi with Safety Relief Valve, Filling Loop and Wall Bracket
KTSSK34SRVNB	3/4" Intafil Combi with Safety Relief Valve

