



ACURA SAFE-TOUCH DUAL OUTLET TMV3 SHOWER ST1030CP

Acura safe-touch dual outlet thermostatic shower with telescopic riser kit, overhead soaker and handset

- Paddle handles to aid users with limited dexterity
- Thermostatic control with anti-scald failsafe technology
- Safe-touch shower body
- Independent control of flow and temperature
- WRAS and TMV3 approved - Complies with NHS D08 & BS7942
- Fast-fix brackets
- Maximum temperature stop



Valve only



Valve only



Product Range

Code	Description
ST1030CP	Acura dual outlet shower with telescopic riser kit, overhead soaker & handset
ST12020CP	Acura dual outlet shower (VALVE ONLY)

Technical Data

Maximum inlet pressure (static):	5 bar
Minimum inlet pressure (dynamic):	0.5 bar
Maximum inlet temperature:	85°C
Factory pre-set temperature:	41°C
Temperature stability:	±2°C
Maximum inlet pressure ratio:	5:1
Minimum temperature differential between hot inlet and mixed outlet to achieve cold water failsafe:	10°C
Valve inlet centres:	150mm
Check valves included:	Yes

Flow Rates

Flow rate (l/min)						
Pressure (bar)	0.5	1	2	3	4	5
Handset	2.4	5.2	8.3	11.7	13.5	15.4
Overhead	2.3	6.9	8.1	12.1	13.5	15.7

Dimensions

