

PRODUCT RANGE

CODE:

TR-PFL15R

TR-PFL22R

TR-PFL28R

TR-PFL35R

TR-PFL42R

TR-PFL54R

DESCRIPTION:

15mm Press-Fit Ball Valve with Blue Lever Handle & Red Sleeve
22mm Press-Fit Ball Valve with Blue Lever Handle & Red Sleeve
28mm Press-Fit Ball Valve with Blue Lever Handle & Red Sleeve
35mm Press-Fit Ball Valve with Blue Lever Handle & Red Sleeve
42mm Press-Fit Ball Valve with Blue Lever Handle & Red Sleeve
54mm Press-Fit Ball Valve with Blue Lever Handle & Red Sleeve



Note: Supplied with both a red & blue sleeves

Technical Specification

Max Operating Pressure 25 Bar
Inlet Temperature Range -20 to 120°C
15 - 35mm Suitable for both M & V jaws
42 - 54mm suitable for V jaws only
Suitable for use with EN1057 Copper, EN10312 Stainless Steel and EN10305-5 Carbon Steel Pipe
Leak before press system
WRAS Approved

Size	DN	ØD	L	L1	L2	H
15	15.2	13.5	64	18	90	47
22	22.2	20	75	20	90	52
28	28.2	25	80	20	115	65
35	35.3	32	116	28	135	76
42	42.3	39.5	138	33	136	85
54	54.3	50	161	39	158	146

