



22mm expansion vessel connection



3/4" female expansion vessel connection



without expansion vessel connection



Additional Information

Includes a balanced cold feed connection

CPR compliant product

300 micron stainless steel mesh filter

Complies to BS EN 12897

Combines a PRV, SRV, check valve and filter in one fitting

Controls inlet pressure to unvented hot water systems

Available with compression, female or no vessel connection

Unvented Group Sets

Description

Unvented Group Set 22mm connection and without expansion vessel connection (SRV 6 Bar)

Unvented Group Set 22mm connections and with 3/4" expansion vessel connection (SRV 6 Bar)

Unvented Group Set 22mm connections and with 22mm expansion vessel connection (SRV 6 Bar)

Unvented Group Set 22mm connections and with 3/4" expansion vessel connection (SRV 4.75 bar)

Code

UVGS21822260.1

UVGS21822210.1

UVGS21822220.1

UVGS21822200.1*

Technical Specification

Max. inlet pressure:	16 bar
Factory Set PRV outlet pressure:	3 bar
SRV discharge pressure:	6 bar or 4.75 bar*
Max. operating temperature:	80°C
Min. operating temperature:	4°C
Max. closing differential of SRV:	20%
Body:	CW602N brass
Strainer:	AISI 304 Stainless Steel
Covers:	PA66 + 30% FV
PRV cartridge:	POM
PRV cartridge internal components:	CW602N UNI EN 12464/65
PRV factory set at	3 bar
SRV supplied in both 6 and 4.75 bar discharge pressure*	

Drawings

