



Product

IT1005CP - Intatherm safe-touch TMV3 thermostatic basin mixer tap with copper tails 7l/min

IT1005CP4 - Intatherm safe-touch TMV3 thermostatic basin mixer tap with copper tails 4l/min

IT1005FT - Intatherm safe-touch TMV3 thermostatic basin mixer tap with flexible tails 7l/min

IT1005FT4 - Intatherm safe-touch TMV3 thermostatic basin mixer tap with flexible tails 4l/min

IT1006CP - Intatherm safe-touch TMV3 thermostatic basin mixer tap with extended lever copper tails 7l/min

IT1006CP4 - Intatherm safe-touch TMV3 thermostatic basin mixer tap with extended lever copper tails 4l/min

Technical Specification

Max Inlet Pressure (static):	10 Bar
Min Inlet Pressure (dynamic):	0.2 Bar
Max Inlet Temperature:	85°C
Factory Pre-set Temperature:	43°C with max temp stop
Temperature Stability:	+/-2°C
Inlet Connections:	M10 / 1/2" Tails
Min temperature differential to achieve hot or cold failsafe:	10°C
System Installation:	Unvented, Pressurised, Gravity & Combination

Additional Information

Long lever to aid users with limited dexterity

Thermostatic sequential control with anti-scald fail-safe technology

Optional extended lever handle

Available with 350mm copper tails or 400mm flexi tails

7l/min or 4l/min flow regulator options

Self draining spout

WRAS & TMV3 Approved

