



22mm expansion vessel connection



3/4" female expansion vessel connection



without expansion vessel connection



## Additional Information

Includes a balanced cold feed connection

CPR compliant product

300 micron stainless steel mesh filter

Complies to BS EN 12897

Combines a PRV, SRV, check valve and filter in one fitting

Controls inlet pressure to unvented hot water systems

Available with compression, female or no vessel connection

## Unvented Group Sets

### Description

Unvented Group Set 22mm connection and without expansion vessel connection (SRV 6 Bar)

Unvented Group Set 22mm connections and with 3/4" expansion vessel connection (SRV 6 Bar)

Unvented Group Set 22mm connections and with 22mm expansion vessel connection (SRV 6 Bar)

Unvented Group Set 22mm connections and with 3/4" expansion vessel connection (SRV 4.75 bar)

### Code

UVGS21822260.1

UVGS21822210.1

UVGS21822220.1

UVGS21822200.1\*

## Technical Specification

Max. inlet pressure:	16 bar
Factory Set PRV outlet pressure:	3 bar
SRV discharge pressure:	6 bar or 4.75 bar*
Max. operating temperature:	80°C
Min. operating temperature:	4°C
Max. closing differential of SRV:	20%
Body:	CW602N brass
Strainer:	AISI 304 Stainless Steel
Covers:	PA66 + 30% FV
PRV cartridge:	POM
PRV cartridge internal components:	CW602N UNI EN 12464/65
PRV factory set at	3 bar
SRV supplied in both	6 and 4.75 bar discharge pressure*

## Drawings

